

In the specification:

Page 2, before "Background of the Invention" insert the following:

CROSS-REFERENCE TO A RELATED APPLICATION

Patent application serial no. 10/719,753 contains a subject matter which is similar to a subject matter of the present application.

Please amend the paragraph bridging pages 8 and 9 as follows:

For adjustment of the cutting depth to the machine, the support plate 16 is turnable about a turning axle which is fixed on the machine housing 10 forwardly on the circular saw blade 14 as seen in a working direction. The selected turning position is fixed by an adjusting device 17. A second adjusting device 17 is arranged on the support plate 18, and by turning the support plate 16 around a longitudinal axis extending parallel to the saw blade plane, enables a cutting angle adjustment of the power tool.

Page 10 amend the paragraph in lines 4-18 as follows:

The bracket handle 21 is hollow and has an inlet 22 which is open to the interior of the protective hood 15 as shown in Figures 3 and 4. It also has an outlet 23 arranged behind the handle region 211 as shown in Figures 1 and 2. Preferably the outlet 23 is located at or near the end of the bracket handle 21 which faces away from the inlet 22. The outlet 23 is closedenclosed by an outlet pipe 24 which can be formed preferably turnable. For the air cooling of the electric motor, the motor housing 12 has air inlet slots 25 shown in Figure 25. Air which is aspirated by a not shown air impeller connected for rotation with the driven shaft of the electric motor is aspirated through the air inlet slots. The air which is aspirated by the air impeller passes through the electric motor and is blown out as a heat-withdrawing motor spent air, and it is guided so that it flows into the inlet 22 of the hollow bracket handle 21. For this purpose an air passage 26 is formed in the housing 10. It expands toward the inlet 22 of the bracket handle 21 and opens into the inlet 22 as shown in Figure 3.

Page 13, amend the paragraph in lines 10-14 as follows:

In a modification of the above mentioned electric hand circular power saw, the bracket handle 21 is turnable about the inlet 22 which opens to the protective hood 15 and is arrestable in an-arbitrary or predetermined turning positions. Thereby in addition to the possibility for adjustment of the dust throwing direction, also an ergonomic effect can be produced.

Amend the paragraph bridging pages 13 and 14 as follows:

The present invention is not limited to the above described electric hand circular power saw. It also can be used for all hand-guided electric power tool with the rotatable tools, such as, for example, masonry mills?mills, rock saws, and angle grinders, concrete grinders, eccentric grinders, etc.